

# MACROAIR CONTROLLERS



## STANDARD FEATURES

- Designed to work with all MacroAir fan models
- Provides a single point for individual fan control
- Fans are daisy chained to the MacroAirController
- The MacroAirController can be located over a thousand feet from a fan
- Secure remote login to the MacroAirController via computer or smart device
- Password protection capabilities
- Individual fan naming option
- Includes 110-240 V power supply



Features	MacroAirController 6	MacroAirController 30
# Fans Controlled	Up to 6 fans	Up to 30 fans
Front Panel Dimensions	5.6 x 4.1 x 0.3 in (W x H x D) / 143 x 103 x 7 mm (W x H x D)	11 x 9 x 0.3 in (W x H x D) / 280 x 228 x 7 mm (W x H x D)
Mounting Depth	1.7 in / 43 mm (3.9 in / 100 mm including clearance)	1.7 in / 44 mm (5.7 in / 144 mm including clearance)
Weight	1.1 lb / 0.5 kg	3.3 lb / 1.5 kg
Serial Port COM1	RS485 Communication	
Power Supply	110-240 V	
Display	TFT-LCD, 480 x 272 pixels, 16.7 million colors	TFT-LCD, 640 x 480 pixels, 16.7 million colors
Active Area of Display	3.7 x 2.1 in (W x H) / 95.0 x 53.9 mm (W x H)	8.3 x 6.2 in (W x H) / 211.2 x 158.4 mm (W x H)
Operating Temperature	14° to 140°F / -10° to +60°C	

**MacroAir Controller requires one Repeater for every 5 fans.**

**Note:** If using a MacroAir Controller, individual Touchpad and AirLynk are not applicable.